



(12) **United States Patent**  
**Rojer**

(10) **Patent No.:** **US 7,747,937 B2**  
(45) **Date of Patent:** **Jun. 29, 2010**

(54) **WEB BOOKMARK MANAGER**

(76) Inventor: **Alan S. Rojer**, 423 Walton Rd.,  
Maplewood, NJ (US) 07040-1119

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 992 days.

(21) Appl. No.: **11/503,047**

(22) Filed: **Aug. 11, 2006**

(65) **Prior Publication Data**

US 2007/0043745 A1 Feb. 22, 2007

**Related U.S. Application Data**

(60) Provisional application No. 60/708,534, filed on Aug.  
16, 2005.

(51) **Int. Cl.**  
**G06F 17/27** (2006.01)

(52) **U.S. Cl.** ..... **715/206**

(58) **Field of Classification Search** ..... **715/273,**  
**715/206**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,115,504	A	5/1992	Belove et al.	
5,309,359	A	5/1994	Katz et al.	
5,423,032	A	6/1995	Byrd et al.	
5,434,777	A	7/1995	Luciw	
5,463,773	A *	10/1995	Sakakibara et al.	707/102
5,544,360	A	8/1996	Lewak et al.	
5,774,888	A	6/1998	Light	
5,819,258	A	10/1998	Vaithyanathan et al.	
5,819,260	A	10/1998	Lu et al.	
5,842,217	A	11/1998	Light	
5,878,406	A *	3/1999	Noyes	706/55
5,917,491	A *	6/1999	Bauersfeld	715/810
5,963,965	A	10/1999	Vogel	
6,026,410	A *	2/2000	Allen et al.	707/104.1
6,038,560	A *	3/2000	Wical	707/5

6,100,890	A	8/2000	Bates et al.	
6,138,128	A *	10/2000	Perkowitz et al.	715/205
6,208,995	B1 *	3/2001	Himmel et al.	707/104.1
6,212,522	B1 *	4/2001	Himmel et al.	707/10
6,223,178	B1 *	4/2001	Himmel et al.	707/10
6,247,021	B1 *	6/2001	Himmel et al.	707/104.1
6,334,131	B2	12/2001	Chakrabarti et al.	

(Continued)

**OTHER PUBLICATIONS**

Borkar et al, Automatic Segmentation of Text Into Structured  
Records, May 21-24, 2001, ACM SIGMOD, pp. 175-185.\*


(Continued)

*Primary Examiner*—Doug Hutton  
*Assistant Examiner*—Frank D Mills

(57) **ABSTRACT**

A web bookmark manager processes a collection of web  
bookmarks to produce a richly structured presentation of the  
bookmark collection. The bookmark collection includes rep-  
resentations of resources, topics, and notice events. A notice  
event includes a reference to a web resource and a natural  
language description provided by a user. The notice descrip-  
tion is processed by a classifier to determine topics to which  
the referenced web resource shall be associated. The process-  
ing of the notice description includes parsing to obtain  
sequences of content words, to which topics are associated.  
Generalizations of a topic are determined by subsequences of  
the associated word sequence. The presentation of a collec-  
tion of bookmarks includes a chronology of notices, a ranking  
of topics, a taxonomy of topics, and an index of content words  
from topics. The presentation further includes per-topic and  
per-resource presentations.

**19 Claims, 16 Drawing Sheets**



## U.S. PATENT DOCUMENTS

6,360,227	B1 *	3/2002	Aggarwal et al. ....	707/102
6,389,412	B1	5/2002	Light	
6,424,982	B1	7/2002	Vogel	
6,427,175	B1 *	7/2002	Khan et al. ....	709/245
6,493,702	B1 *	12/2002	Adar et al. ....	707/3
6,519,602	B2	2/2003	Sundaresan et al.	
6,549,217	B1 *	4/2003	De Greef et al. ....	715/745
6,571,240	B1	5/2003	Ho et al.	
6,631,496	B1 *	10/2003	Li et al. ....	715/200
6,721,728	B2	4/2004	McGreevy	
6,810,395	B1 *	10/2004	Bharat	707/4
6,832,350	B1	12/2004	Bates et al.	
6,934,718	B2	8/2005	Davidsson	
6,961,751	B1 *	11/2005	Bates et al. ....	707/10
7,100,114	B1	8/2006	Burleson	
7,167,901	B1	1/2007	Beadle et al.	
7,203,909	B1 *	4/2007	Horvitz et al. ....	715/765
2002/0016786	A1 *	2/2002	Pitkow et al. ....	707/3
2002/0033847	A1	3/2002	Masthoff	
2002/0099784	A1 *	7/2002	Tran	709/212
2003/0042690	A1 *	3/2003	Oki et al. ....	277/628
2003/0101413	A1 *	5/2003	Klein et al. ....	715/513
2004/0054677	A1	3/2004	Mueller et al.	
2004/0088158	A1 *	5/2004	Sheu et al. ....	704/9
2004/0205499	A1	10/2004	Gupta	
2005/0050069	A1 *	3/2005	Vaschillo et al. ....	707/100
2005/0267869	A1 *	12/2005	Horvitz et al. ....	707/2
2006/0015509	A1 *	1/2006	Naitou	707/10
2006/0161423	A1 *	7/2006	Scott et al. ....	704/10
2006/0224608	A1 *	10/2006	Zamir et al. ....	707/101
2006/0265381	A1 *	11/2006	Altat et al. ....	707/10

## OTHER PUBLICATIONS

Joel L. Fagan, Automatic Phrase Indexing for Document Retrieval, Proc. 10th ACM SGIR Conf., New Orleans, LA, 1987, pp. 91-101.

Gerard Salton, Automatic Text Indexing Using Complex Identifiers, Proc. ACM Conf. Document Processing Systems, Santa Fe, NM, 1988, 135-144.

W. Bruce Croft et al., The Use of Phrases and Structured Queries in Information Retrieval, ACM Conf. on R=D in Information Retrieval, Chicago, IL, 1991, pp. 32-45.

Yoelle S. Maarek et al., Automatically Organizing Bookmarks per Contents, Computer Networks and ISDN Systems, vol. 28, Issues 7-11, 1996, p. 1321.

David Abrams et al. Information Archiving with Bookmarks, Proc. SIGCHI, LA, CA, 1998, pp. 41-48.

Fred L. Drake, The XML Bookmark Exchange Language, 1998, CNRI, <http://pyxml.sourceforge.net/topics/xbel>, downloaded Aug. 1, 2006.

Mark Sanderson et al. Deriving concept hierarchies from text, Proc. SIGIR, Berkeley, CA, 1999, pp. 206-213.

Eytan Adar et al. Haystack: Per-User Information Environments, Proc. 8th IKM, KC, MO, 1999, pp. 413-422.

Susan Dumais et al. Stuff I've Seen, Proc. SIGIR, Toronto, Canada, 2003, pp. 72-79.

Adam Mathes, Folksonomies, 2004, <http://www.adammathes.com/academic/computer-mediated-communication/folksonomies.html>, downloaded Jul. 20, 2006.

Tony Hammond et al. Social Bookmarking Tools (I), D-Lib Magazine, vol. 11, No. 5, Apr. 2005, <http://www.dlib.org/dlib/april05/hammond/04hammond.html>, downloaded Jul. 20, 2006.

Ben Lund et al. Social Bookmarking Tools (II), D-Lib Magazine, vol. 11, No. 4, Apr. 2005, <http://www.dlib.org/dlib/april05/lund/04lund.html>, downloaded Jul. 20, 2006.

Shui-Lung Chuang et al. Taxonomy Generation for Text Segments, ACM Trans. Information Systems, vol. 23, No. 4, Oct. 2005, pp. 363-396.

\* cited by examiner

FIG. 1





FIG. 2



*FIG. 3*

```
Module1068 {  
    Resource1070 {  
        Text _uri1078;  
        Set<Notice1074> _notices1080;  
        Set<Topic1072> _topics1082;  
    }  
    Topic1072 {  
        Text _text1084;  
        Text _id1086;  
        Set<Resource1070> _resources1088;  
        Set<Topic1072> _genera1090;  
        Set<Topic1072> _species1092;  
        Sequence<Word1076> _words1094;  
    }  
    Notice1074 {  
        Text _date1096;  
        Text _description1098;  
        Resource1070 _resource1100;  
        Set<Topic1072> _topics1102;  
    }  
    Word1076 {  
        Text _text1104;  
        Text _id1106;  
        Set<Topic1072> _topics1108;  
    }  
}
```


FIG. 4

```

Portfolio1002 {
    // collected instances...
    Set<Notice1074> _notices1020;
    Set<Resource1070> _resources1024;
    Set<Topic1072> _topics1022;
    Set<Word1076> _words1110;
    // classification services...
    Word1076 canonical_word1112(Text);
    Map<Text, Word1076> text_word1114;
    Topic1072 canonical_topic1116(Topic1072);
    Map<Text, Topic1072> text_topic1118;
    void topic_genera1120(Topic1072);
    // etc...
    Boolean topic_is_trivial1122();
};

```

FIG. 5



*FIG. 6***1124 Discourse Language Relations**

1126 is-word  
    1128 word-has-text  
    1130 word-has-topic  
1132 is-topic  
    1134 topic-has-text  
    1136 topic-has-word  
    1138 topic-has-genus  
    1140 topic-has-species  
    1142 topic-has-resource  
1144 is-notice  
    1146 notice-has-date  
    1148 notice-has-resource  
    1150 notice-has-description  
    1152 notice-has-topic  
1154 is-resource  
    1156 resource-has-notice  
    1158 resource-has-topic

*FIG. 7***1160 Words Discourse**

Word-web is-word<sup>1126</sup>; word-has-text<sup>1128</sup> web.  
Word-based is-word<sup>1126</sup>; word-has-text<sup>1128</sup> based.  
Word-manager is-word<sup>1126</sup>; word-has-text<sup>1128</sup> manager.

FIG. 8

**1162 Topics Discourse**

```
Topic-web-based-manager is-topic1132;  
  topic-has-text1134 'web based manager';  
  topic-has-word1136 Word-web, Word-based, Word-manager;  
  topic-has-genus1138 Topic-web-based, Topic-based-manager.  
Topic-web-based is-topic1132;  
  topic-has-text1134 'web based';  
  topic-has-word1136 Word-web, Word-based;  
  topic-has-genus1138 Topic-web, Topic-based.
```

FIG. 9

**1164 Resources Discourse**

```
'http://www.n-gon.com/freshmeat/b./'  
resource-has-notice1156  
  {  
    notice-has-date1146 2001-10-22;  
    notice-has-description1150  
      'Web-based manager for bookmarks using XML, Perl';  
    notice-has-topic1152 Topic-b, Topic-web-based-manager,  
      Topic-bookmarks-using-xml, Topic-perl  
  },  
  {  
    notice-has-date1146 2003-09-22;  
    notice-has-description1150 'b. -- web-based bookmark manager';  
    notice-has-topic1152 Topic-b, Topic-web-based-bookmark-manager  
  }.
```



FIG. 10

**1006 Notices Discourse**

```
{  
  notice-has-date1146 2001-10-22;  
  notice-has-resource1148  
    'http://www.n-gon.com/freshmeat/b./';  
  notice-has-description1150  
    'b. -- Web-based manager for bookmarks using XML, Perl'  
}.  
{  
  notice-has-date1146 2002-02-25;  
  notice-has-resource1148  
    'http://www.public.iastate.edu/~CYBERSTACKS/CTW.htm';  
  notice-has-description1150  
    'Beyond Bookmarks: Schemes for Organizing the Web'  
}.
```

FIG. 11




FIG. 12

```
writer1028(Portfolio1002 portfolio, bookmArchive1026 archive)
// write words...
open archive.words-discourse1160;
foreach Word1076 word in portfolio._words1110
    write word._id1106, is-word1126,
        word-has-text1128, word._text1104;
close archive.words-discourse1160;
// write topics...
open archive.topics-discourse1162;
foreach Topic1072 topic in portfolio._topics1022 {
    write topic._id1086, is-topic1132,
        topic-has-text1134, topic._text1084;
    if (topic._words1094)
        write topic-has-word1136;
        foreach Word1076 word in topic._words1094
            write word._id1106;
    if (topic._genera1090) {
        write topic-has-genus1138;
        foreach Topic1072 genus in topic._genera1090
            write genus._id1086;
    }
close archive.topics-discourse1162;
// write resources...
open archive.resources-discourse1164;
foreach Resource1070 resource in portfolio._resources1024
    write resource._uri1078, is-resource1154;
    if (resource._notices1080)
        write resource-has-notice1156;
        foreach Notice1074 notice in resource._notices1080
            write notice-has-date1146, notice._date1096;
            write notice-has-description1150, notice._description1098;
            if (notice._topics1102)
                write notice-has-topic1152;
                foreach Topic1072 topic in notice._topics1102
                    write topic._id1086;
close archive.resources-discourse1164;
```

FIG. 13




FIG. 14

**1168 Instantiators**

Instantiator	Characteristic	Category
WordInstantiator <sup>1176</sup>	is-word <sup>1126</sup>	Word <sup>1038</sup>
TopicInstantiator <sup>1178</sup>	is-topic <sup>1132</sup>	Topic <sup>1018</sup>
ResourceInstantiator <sup>1180</sup>	is-resource <sup>1154</sup>	Resource <sup>1010</sup>
NoticeInstantiator <sup>1182</sup>	is-notice <sup>1144</sup>	Notice <sup>1004</sup>

FIG. 15

**1170 Text Receivers**

TextReceiver	Characteristic	Property
WordIdReceiver <sup>1184</sup>	is-word <sup>1126</sup>	WordID <sup>1064</sup>
TopicIdReceiver <sup>1186</sup>	is-topic <sup>1132</sup>	TopicID <sup>1052</sup>
ResourceUriReceiver <sup>1188</sup>	is-resource <sup>1154</sup>	ResourceURI <sup>1044</sup>

FIG. 16

**1172 Assignors**

<b>Assignor</b>	<b>Relation</b>	<b>Property</b>
WordTextAssignor <sup>1190</sup>	word-has-text <sup>1128</sup>	WordText <sup>1062</sup>
TopicTextAssignor <sup>1192</sup>	topic-has-text <sup>1134</sup>	TopicText <sup>1050</sup>
NoticeDateAssignor <sup>1194</sup>	notice-has-date <sup>1146</sup>	NoticeDate <sup>1040</sup>
NoticeDescriptionAssignor <sup>1196</sup>	notice-has-description <sup>1150</sup>	NoticeDescription <sup>1012</sup>

FIG. 17

**1174 Associators**

<b>Associator</b>	<b>Relation</b>	<b>Association</b>
WordTopicAssociator <sup>1198</sup>	word-has-topic <sup>1130</sup>	WordTopics <sup>1066</sup>
TopicGenusAssociator <sup>1200</sup>	topic-has-genus <sup>1138</sup>	TopicGenera <sup>1056</sup>
TopicSpeciesAssociator <sup>1202</sup>	topic-has-species <sup>1140</sup>	TopicSpecies <sup>1058</sup>
TopicResourcesAssociator <sup>1204</sup>	topic-has-resource <sup>1142</sup>	TopicResources <sup>1054</sup>
TopicWordAssociator <sup>1206</sup>	topic-has-word <sup>1136</sup>	TopicWords <sup>1060</sup>
NoticeResourceAssociator <sup>1208</sup>	notice-has-resource <sup>1148</sup>	NoticeResource <sup>1008</sup>
NoticeTopicAssociator <sup>1210</sup>	notice-has-topic <sup>1152</sup>	NoticeTopics <sup>1042</sup>
ResourceNoticeAssociator <sup>1212</sup>	resource-has-notice <sup>1156</sup>	ResourceNotices <sup>1046</sup>
ResourceTopicAssociator <sup>1214</sup>	resource-has-topic <sup>1158</sup>	ResourceTopics <sup>1048</sup>

FIG. 18

TopicSpecies<sup>1058</sup> complements TopicGenera<sup>1056</sup>.  
TopicResources<sup>1054</sup> complements ResourceTopics<sup>1048</sup>.  
TopicWords<sup>1060</sup> complements WordTopics<sup>1066</sup>.  
ResourceNotices<sup>1046</sup> complements NoticeResource<sup>1008</sup>.

FIG. 19




FIG. 20

**1218 Classifier Grammar**

```

start1230 : ~
| start1230 topic1232 /* accept topic */
| start1230 topic1232 stop1234 /* accept tailed topic */
| start1230 topic1232 WHITE1220 /* accept tailed topic */
| start1230 stop1234
| start1230 WHITE1220
;

topic1232 : CONTENT1228 /* start topic */
| topic1232 WHITE1220 CONTENT1228 /* topic accept content */
| topic1232 DASH1224 CONTENT1228 /* topic accept content */
;

stop1234 : PUNCTUATION1222 | DASH1224 | FUNCTION1226 ;

```

FIG. 21




FIG. 22




FIG. 23

topic-has-genus<sup>1138</sup> is-transitive.  
topic-has-species<sup>1140</sup> is-transitive.

FIG. 24




FIG. 25






FIG. 26




FIG. 27




FIG. 28





FIG. 29



1

**WEB BOOKMARK MANAGER****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims the benefit of PPA Ser. No. 60/708, 534, filed 2005 Aug. 16 by the present inventor, the disclosure of which is incorporated herein by reference.

**BACKGROUND AND OBJECTS OF THE INVENTION**

This invention relates particularly to management of web bookmarks, and generally to management of document assets.

The success of the world wide web has fostered the development of tools to assist users in the task of managing a surfeit of online resources. Web bookmarks, sometimes known as favorites, are one of the oldest tools for managing collections of web resources. Despite many innovations in managing bookmarks, existing systems are variously deficient, as will be described.

Even the oldest web browsers, such as Lynx and Mosaic, provided for management of a limited collection of web bookmarks. The oldest and simplest management mechanism was a flat collection, to which a user could accumulate links to selected online resources. The limitations of a flat collection become apparent as the number of bookmarks starts to exceed a few dozen.

An early innovation to bookmark management was the provision of folders for hierarchical organization of larger collections of bookmarks. In folder-oriented bookmark management, users or systems organize a bookmark collection by analogy to a file system. A folder of bookmarks may contain bookmarks or additional folders. Modern browsers and many third-party systems support folder-oriented bookmark management; such systems will be familiar to those skilled in the art. A notable resource for folder-oriented bookmark management is the XML Bookmark Exchange Language (XBEL), which permits browser-independent interchange of bookmark data. See "The XML Bookmark Exchange Language", by Fred L. Drake, Jr. (1998), available online at <http://pyxml.sourceforge.net/topics/xbel/>.

If the folders are organized according to specialization and generalization relationships (more general folders contain more specific folders), the user may construct a taxonomy for bookmark management, which is potentially very useful. The folder hierarchy provides a limited taxonomy since it permits only a single generalization. Folder-oriented bookmark management thus lack convenient native support for multiple generalizations in a taxonomy. XBEL and other systems augment the folder scheme with aliasing to permit a bookmark to be assigned to multiple folders, thereby alleviating to some extent the disadvantage that a singleton-genus taxonomy imposes.

Folder-oriented bookmark management permits management of arbitrarily large bookmark collections, but it imposes substantial disadvantages for the user when bookmarks are captured and retrieved. At capture time, the user must select a folder destination for a new bookmark, thus performing a classification task. At retrieval time, the user must determine the folder in which a desired bookmark resides, potentially requiring a multistep traversal of the bookmark folder hierarchy. These are non-trivial operations, especially when the bookmark collection is large and the folder hierarchy is several levels deep.

2

To alleviate the disadvantages of folder-oriented bookmark management, many systems have been described to automate classification and/or retrieval in folder-oriented bookmark management. Automatic classification of documents to computed categories has been actively explored in the prior art. The assignment of bookmarks to categories based on the textual content of target resources is a special case of document classification. A beneficial aspect of automatic classification is the provision of a taxonomy, in which topics are related by specialization and generalization. A disadvantage of automatic classification is that the user must substantially cede personalized characterization of a bookmark resource. Since the purposes of the user in collecting bookmarks can hardly be known to the creators of target resources, the loss of personalization cannot be easily remedied by analysis of the target resource contents.

A major advance in managing bookmarks was achieved with the introduction of tagging for bookmark collections. Tags are labels which are associated with sets of bookmarks. Tags function much like keywords; however, in practice, keywords are often associated with controlled vocabularies prepared by experts, while tagging is typically associated with communities of ordinary users. Tagging is closely related to the practice of social bookmarking, in which a community of users share bookmarks. Exemplary systems include Delicious (<http://del.icio.us/>) and Connotea (<http://www.connotea.org/>). A valuable survey of social bookmarking may be found in these papers: "Social Bookmarking Tools (I): A General Review," by Tony Hammond et. al, D-Lib Magazine 11(4), April 2005, available online at <http://www.dlib.org/dlib/april05/hammond/04hammond.html>; and "Social Bookmarking Tools (II): A Case Study—Connotea," by Ben Lund et. al, D-Lib Magazine 11(4), April 2005, available online at <http://www.dlib.org/dlib/april05/lund/04lund.html>.

Tagging alleviates the inconvenience of directly managing folders without the penalty of ceding classification to an automatic process, but the loss of a taxonomy due to the flatness of tags is disadvantageous. Moreover, tag assignment does not exploit the flexibility of natural language descriptions; obtaining a precise description of the relevance of a bookmark resource without the expressive subtlety of natural language may be difficult or impossible. Furthermore, the capability for description is available to every literate user of natural language, while effective tagging is a skill that must be acquired.

In view of the disadvantages attaching to bookmark managers in the prior art, alternatives to existing bookmark managers are desirable. An object of the present invention is to gain many of the benefits of automatic classification, including automatic computation of a taxonomy, without sacrificing the capability for user-specific personalization. Another object of the present invention is to accommodate the full expressive power of natural language in description and classification of bookmark resources. Another object is to provide a representation of a bookmark collection which is convenient for automatic processing. Another object is to provide a richly structured presentation of a bookmark collection which is convenient for browsing and informal search.

**SUMMARY**

A web bookmark manager processes a collection of web bookmarks to produce a richly structured presentation of the bookmark collection. The bookmark collection includes representations of resources, topics, and notice events. A notice event includes a reference to a web resource and a natural language description provided by a user. The notice descrip-

tion is processed by a classifier to determine topics to which the referenced web resource shall be associated. The processing of the notice description includes parsing to obtain sequences of content words, to which topics are associated. Generalizations of a topic are determined by subsequences of the associated word sequence. The presentation of a collection of bookmarks includes a chronology of notices, a ranking of topics, a taxonomy of topics, and an index of content words from topics. The presentation further includes per-topic and per-resource presentations.

### BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 depicts an exemplary web bookmark manager.  
 FIG. 2 depicts an exemplary model for representation of a collection of web bookmarks.  
 FIG. 3 depicts exemplary C++ class skeletons for representation of elements of a collection of web bookmarks.  
 FIG. 4 depicts an exemplary C++ class skeleton providing an object-oriented representation of a collection of web bookmarks.  
 FIG. 5 depicts an exemplary computation of genera from a topic.  
 FIG. 6 depicts relations that characterize an exemplary declarative language representing a bookmark collection.  
 FIG. 7 depicts an exemplary declarative discourse representing words.  
 FIG. 8 depicts an exemplary declarative discourse representing topics.  
 FIG. 9 depicts an exemplary declarative discourse representing resources.  
 FIG. 10 depicts an exemplary declarative discourse representing notices.  
 FIG. 11 depicts the context for an exemplary writer which views a portfolio and writes an archive.  
 FIG. 12 depicts an exemplary writer which views an object-oriented representation of a collection of web bookmarks and writes an archive.  
 FIG. 13 depicts an exemplary reader which constructs an object-oriented representation of a collection of web bookmarks from a declarative discourse.  
 FIG. 14 depicts exemplary instantiators, the characteristic relations to which they are responsive, and the categories for which they provide instances.  
 FIG. 15 depicts exemplary text receivers, the characteristic relations to which they are responsive, and the properties for which they receive entity text.  
 FIG. 16 depicts exemplary assignors, the relations to which they are responsive, and the properties for which they provide assignments.  
 FIG. 17 depicts exemplary associators, the relations to which they are responsive, and the associations which they implement.  
 FIG. 18 depicts exemplary declarations establishing meta relations in the dispatcher.  
 FIG. 19 depicts an exemplary updater in which a notices discourse is read and a portfolio is edited to incorporate the notices.  
 FIG. 20 depicts an exemplary grammar for an exemplary classifier which computes topics from notice descriptions.  
 FIG. 21 depicts an example of the exemplary classifier processing a description in natural language to several topics.  
 FIG. 22 depicts an exemplary presenter, which reads an archive, edits a portfolio, and writes a presentation.  
 FIG. 23 depicts exemplary declarations establishing meta relations in the closure dispatcher.

FIG. 24 depicts an exemplary presentation of a chronology of notices from a bookmark collection.

FIG. 25 depicts an exemplary presentation of a resource from a bookmark collection.

FIG. 26 depicts an exemplary presentation of a topic from a bookmark collection.

FIG. 27 depicts an exemplary presentation of a ranking of topics for a bookmark collection.

FIG. 28 depicts an exemplary presentation of a taxonomy of topics for a bookmark collection.

FIG. 29 depicts an exemplary presentation of an index of topics for a bookmark collection.

### DETAILED DESCRIPTION

#### 1 Terminology

Various embodiments of the web bookmark manager may be provided in various configurations of hardware and software. A particular configuration of hardware and software is denoted a platform. Many particular aspects of an embodiment are determined by the particular characteristics of the platform. However, certain aspects of the web bookmark manager are independent of platform; to precisely characterize these aspects requires a platform-independent terminology: instance, category, feature, and model, as defined below.

An instance represents a particular element; an instance is characterized by its membership in one or more categories. A category represents a set of instances which have features in common. Examples of categories in the bookmark manager include notices, topics, and resources. A feature represents a common aspect of the instances of a category. The collection of features shared by the instances of a category are characteristic of the category. A model is a collection of categories, in which the categories may be interrelated by their features.

Features include properties and associations. A property represents the attachment of one or more scalar values to a particular instance. A scalar value is a quantity that is fully specified by its value; examples include numbers, dates, and text (strings). Typical properties include identifiers, descriptions, dates, and counts.

An association represents an interrelation between instances. Typical associations interrelate notices to resources, resources to topics, and topics to more or less general topics. An association may stand in relationship to another association; in particular, an association may have a complement. An association F is complementary to an association G if, for any pair of instances a, b, when a is F-associated to b, b is G-associated to a. An example of a pair of complementary associations is "has-parent" and "has-child". An association may be transitive. In a transitive association H, if, for any triple of instances a, b, c, when a is H-associated with b, and b is H-associated with c, then a is H-associated with c. An example of a transitive association is "has-ancestor".

To summarize, a model is characterized by a collection of categories. A category is characterized by a collection of features. Features include properties and associations. Properties attach scalar values to instances. Associations attach instances to instances. An instance is characterized by membership in one or more categories. The membership of an instance in a category is indicative of the features which are applicable to the instance.

A model describes potentialities. The categories in a model are representative of instances. The features in the categories are representative of characteristics of instances. A model is useful as a precise description and even potentially as a source

## 5

for code generation and other useful products, but for most purposes, a model is utilized implicitly by operations on instantiations of the model. An instantiation of a model includes representation of instances from the categories of the model and specifications of features for those instances. A model typically permits an unbounded collection of instantiations. Moreover, a particular instantiation of some model may exist in many distinct media. Such media include a data structure of interlinked objects in random-access memory, rows in a relational database, sequential text utilizing the XML metalanguage in an operating system file, a customized text format in a file, or a proprietary binary data format in a file. An implementation of a model is a collection of facilities permitting instantiations of the model. An implementation may take the form of a collection of classes in a programming language, a schema in a database, a document type definition for XML markup, a formal language for processing textual representations, etc.

An important aspect of the bookmark manager is the classification of resources to topics according to natural language descriptions of the resources. A topic represents a set of associated resources. Topics may be organized according to generalization and specialization. A first topic generalizes a second topic when every associated resource of the second topic is also associated with the first topic. Alternatively, the first topic is denoted a genus of the second topic. Conversely, a first topic specializes a second topic when every associated resource of the first topic is also associated with the second topic. Alternatively, the first topic is denoted a species of the second topic. Generalization and specialization are complementary; if a first topic generalizes a second topic, the second topic specializes the first topic. Generalization and specialization are also transitive. When a first topic generalizes a second topic, and the second topic generalizes a third topic, the first topic generalizes the third topic. Similarly for specialization. A collection of topics related by generalization and specialization is denoted a taxonomy. A presentation of a taxonomy is denoted a thesaurus.

The classification of resources to topics by processing natural language descriptions makes use of parsing, in which the text of a natural language description is lexically analyzed to obtain tokens. The tokens are subsequently syntactically analyzed according to grammatical rules. The tokens determined by lexical analysis are associated with textual elements. These textual elements may be further processed for standardization by standardizing letter case, stemming, and even substitution of synonyms. Standardized textual elements are denoted word types. A sequence of standardized textual elements is denoted a phrase; phrases are associated with topics. When a phrase has a nonempty subsequence, the topic associated with the nonempty subsequence is associated as a generalization of the topic associated with the original phrase.

## 2 Overview

FIG. 1 depicts an exemplary web bookmark manager. A bookmark manager **1000** consists of representations and computations useful for the management of a collection of web bookmarks. A portfolio **1002** represents a collection of web bookmarks. A user, upon taking notice of an interesting web resource, provides an instance of a notice-category **1004**, which is collected along with other notices in a notices-discourse **1006**. The notice-category **1004** includes a notice-resource-association **1008**, which is associated with a representation of the web resource; the web resource is represented by an instance of a resource-category **1010**. The notice-category **1004** further includes a notice-description-property

## 6

**1012**, which is a natural language description of the web resource, ideally taking particular note of the relevance of the web resource to the user's interests.

One or more instances of the notice-category **1004** are integrated into the portfolio **1002** by an updater **1014**. In the updater **1014**, the notice-description-property **1012** is processed by a classifier **1016**, which may determine one or more instances of a topic-category **1018**. The instances of the notice-category **1004** provided by the user are collected in a portfolio-notices **1020**. The instances of the topic-category **1018** computed from the notice-description-property **1012** are collected in a portfolio-topics **1022**. The instances of the resource-category **1010** representing the web resources noticed by the user are collected in a portfolio-resources **1024**.

The portfolio **1002** is written to an archive **1026** by a writer **1028**. The archive **1026** is read by a reader **1030** to restore the portfolio **1002**. A presenter **1032** creates a presentation **1034**, which presents the contents of the portfolio **1002** in a fashion suitable for review by the user.

## 3 Model

FIG. 2 depicts an exemplary model for representation of a collection of web bookmarks. In an exemplary embodiment of the invention, the bookmark manager **1000** includes a model **1036**, which in turn includes categories and features which are representative of elements of a collection of web bookmarks. The model **1036** includes the resource-category **1010**, an instance of which represents a web resource that has been noticed by a user. The model **1036** further includes the topic-category **1018**, an instance of which represents a classification element for grouping resources. The model **1036** further includes the notice-category **1004**, an instance of which represents the event of a user noticing a web resource. The model **1036** further includes a word-category **1038**, an instance of which represents a word-type element in a standardized form.

An instance of the notice-category **1004** represents the event of a user taking notice of a web resource. The notice-category **1004** has the notice-resource-association **1008** referencing the resource-category **1010**. The notice-resource-association **1008** identifies the instance of the resource-category **1010** which was noticed. The notice-category **1004** has the notice-description-property **1012** representing the user's description of the resource. The notice-category **1004** has a notice-date-property **1040** representing the date upon which the notice event took place. The notice-category **1004** has a plural notice-topics-association **1042** referencing the topic-category **1018**. The notice-topics-association **1042** represents the instances of the topic-category **1018** which are determined by textual analysis of the notice-description-property **1012** of a particular notice by the classifier **1016**.

An instance of the resource-category **1010** represents a web resource that has been noticed by a user. The resource-category **1010** has a resource-URI-property **1044** which uniquely identifies the web resource using a uniform resource identifier (per RFC 2396). The resource-category **1010** has a plural resource-notices-association **1046**, referencing the notice-category **1004**. The resource-notices-association **1046** represents the collection of instances of the notice-category **1004** which took notice of a particular resource instance. The resource-notices-association **1046** is complementary to the notice-resource-association **1008**. The resource-category **1010** has a plural resource-topics-association **1048** referencing the resource-category **1010**. The resource-topics-association **1048** represents the collection of instances of the topic-category **1018** to which a particular resource instance has

been classified. In an alternative embodiment, instances of the topic-category **1018** are indirectly associated with the resource-category **1010** via the resource-topics-association **1046** and the notice-topics-association **1042**.

An instance of the topic-category **1018** represents a classification element for grouping resources. The topic-category **1018** has a topic-text-property **1050** which provides a textual expression of the topic. The topic-category **1018** has a topic-id-property **1052** which uniquely identifies the instance as an entity (for use in the archive **1026**). The topic-text-property **1050** is inadequate as a unique identifier since an instance of the word-category **1038** may have identical text. The topic-category **1018** has a plural topic-resources-association **1054**, referencing the resource-category **1010**. Alternatively, a complement to the notice-topics-association **1042** could be provided in the topic-category **1018**, in which case the associated resources could be indirectly determined via the notice-resource-association **1008**. The topic-resources-association **1054** represents the grouped instances of the resource-category **1010** which have been assigned to a particular topic instance. The topic-resources-association **1054** is complementary to the resource-topics-association **1048**.

The topic-category **1018** has a plural topic-genera-association **1056** referencing the topic-category **1018**. The topic-genera-association **1056** represents a collection of instances of the topic-category **1018** which are more general classification elements relative to a particular topic instance. For a particular topic, the instances of the topic-resources-association **1054** of a genus topic form a superset of the instances of the topic-resources-association **1054** of the particular topic. Equivalently, if a particular topic has a genus topic, than any resource associated with the particular topic is associated with the genus topic, but not necessarily vice versa. The topic-genera-association **1056** is transitive.

The topic-category **1018** has a plural topic-species-association **1058** referencing the topic-category **1018**. The plural topic-species-association **1058** represents a collection of instances of the topic-category **1018** which are more specific classification elements relative to a particular topic instance. For a particular topic, the topic-resources-association **1054** of a species topic form a subset of the topic-resources-association **1054** of the particular topic. Equivalently, if a particular topic has a species topic, than any resource associated with the species topic is associated with the particular topic, but not necessarily vice versa. The topic-species-association **1058** is transitive. The topic-species-association **1058** is complementary to the topic-genera-association **1056**. The topic-genera-association **1056** and the topic-species-association **1058** define a taxonomy of topics.

The topic-category **1018** has a plural topic-words-association **1060**, referencing the word-category **1038**. The topic-words-association **1060** represents the topic as a phrase, in which the phrase constituents are standardized word-type elements.

An instance of the word-category **1038** represents a word-type element in a standardized form. The standardized form may include normalization of case (capitalization), stemming (e.g., normalization of markers of the plural, gerunds, tense, etc.) and substitution of synonyms. The word-category **1038** has a word-text-property **1062** which represents the standardized form of the word-type element which is represented by the word instance. The word-category **1038** has a word-id-property **1064** which uniquely identifies the instance as an entity. The word-text-property **1062** is inadequate as a unique identifier since an instance of the topic-category **1018** may have identical text. The word-category **1038** has a plural word-topics-association **1066** referencing the topic-category

**1018**. For a particular word, the word-topics-association **1066** represents the instances of the topic-category **1018** which incorporate the particular word instance as part of the topic instance's self-representation as a phrase. The word-topics-association **1066** is complementary to the topic-words-association **1060**.

In an alternative embodiment, the word-category **1038** may be defined as a specialization of the topic-category **1018**, corresponding to a singleton sequence of instances of the word-category **1038**.

#### 4 Module

In an exemplary embodiment of the invention, the book-mark manager **1000** includes a module **1068**, which implements the categories and features of the model **1036** using C++ classes. The model **1036** includes categories and features of those categories. In an exemplary embodiment, a category is represented by a C++ class. The features of the category are represented by the members of the corresponding class. At run time, an instance of a category is represented by an object instantiated by invocation of a constructor of the corresponding class. Assignment to a member of the object corresponds to specification of a property or an association of the instance. A collection of web bookmarks may thus be represented by an object-oriented data structure. The data structure includes objects from the module's classes, corresponding to instances of the categories. The members of the objects are populated in correspondence to properties and associations of the category instances.

FIG. 3 depicts exemplary C++ class skeletons for representation of elements of a collection of web bookmarks. The module **1068** includes classes implementing the categories of the model **1036**. A resource-class **1070** implements the resource-category **1010**. A topic-class **1072** implements the topic-category **1018**. A notice-class **1074** implements the notice-category **1004**. A word-class **1076** implements the word-category **1038**.

The resource-class **1070** implements the resource-category **1010**. The resource-class **1070** has a resource-URI-text **1078**, implementing the resource-URI-property **1044**. The resource-class **1070** has a resource-notices-set **1080**, implementing the resource-notices-association **1046**. The resource-notices-set **1080** refers to objects of the notice-class **1074**. The resource-class **1070** has a resource-topics-set **1082**, implementing the resource-topics-association **1048**. The resource-topics-set **1082** refers to objects of the topic-class **1072**.

The topic-class **1072** implements the topic-category **1018**. The topic-class **1072** has a topic-text-text **1084**, implementing the topic-text-property **1050**. The topic-class **1072** has a topic-id-text **1086**, implementing the topic-id-property **1052**. The topic-class **1072** has a topic-resources-set **1088**, implementing the topic-resources-association **1054**. The topic-resources-set **1088** refers to objects of the resource-class **1070**. The topic-class **1072** has a topic-genera-set **1090** implementing the topic-genera-association **1056**. The topic-genera-set **1090** refers to objects of the topic-class **1072**. The topic-class **1072** has a topic-species-set **1092** implementing the topic-species-association **1058**. The topic-species-set **1092** refers to objects of the topic-class **1072**. The topic-class **1072** has a topic-words-sequence **1094**, implementing the topic-words-association **1060**. The topic-words-sequence **1094** refers to objects of the word-class **1076**.

The notice-class **1074** implements the notice-category **1004**. The notice-class **1074** has a notice-date-text **1096**, implementing the notice-date-property **1040**. The notice-class **1074** has a notice-description-text **1098**, implementing

the notice-description-property **1012**. The notice-class **1074** has a notice-resource-reference **1100**, implementing the notice-resource-association **1008**. The notice-resource-reference **1100** refers to an object of the resource-class **1070**. The notice-class **1074** has a notice-topics-set **1102**, implementing the notice-topics-set **1102**. The notice-topics-set **1102** refers to objects of the topic-class **1072**.

The word-class **1076** implements the word-category **1038**. The word-class **1076** has a word-text-text **1104**, implementing the word-text-property **1062**. The word-class **1076** object has a word-id-text **1106**, implementing the word-id-property **1064**. The word-class **1076** has a word-topics-set **1108**, implementing the word-topics-association **1066**. The word-topics-set **1108** refers to objects of the topic-class **1072**.

#### 5 Alternatives to Module

In an exemplary embodiment the module **1068** implements the model **1036**. The module **1068** permits instantiation of the model **1036** as an object-oriented data structure, where the objects are constructed via C++ classes. Other programming languages could be used to implement the model; implementations in C# or JAVA would closely follow the C++ module. For a scripting language such as Perl, Python, or Ruby, some details would need adaptation, such as provision for a set. To implement the model using a non-object-oriented language would require additional efforts but no particular difficulties for one skilled in the art.

Other embodiments may be also provided which implement the model **1036** in representations that are not directly compatible with a programming language. An instantiation of the model **1036** may be represented with a declarative discourse, as will be described below, in which case the instantiation has a textual representation which may be stored on a persistent digital medium such as a CD-ROM or a hard disk.

An instantiation of the model **1036** may be provided using an XML expression. In such an expression, instances of the categories of the model **1036** are represented by tagged XML elements. Properties and associations of the instances of the categories are represented by a combination of attributes and tagged XML elements.

An instantiation of the model **1036** may be provided using a relational database. Categories of the model **1036** are implemented as tables; each row of such a table represents an instance of a category. The singleton properties and associations of the model **1036** are implemented with columns of the table representing the category. A plural property or association is implemented by an additional table using a foreign key to refer to the subject instances and, in case of associations, object instance.

#### 6 Portfolio

In an exemplary embodiment, the bookmark manager **1000** includes the portfolio **1002**, a C++ class which represents a collection of web bookmarks as an interlinked object-oriented data structure, the elements of which are instantiated from the classes of the module **1068**. An instance of the portfolio **1002** represents an instantiation of the model **1036**, in which instances from the categories of the model **1036**, implemented by objects from the classes of the module **1068**, are provided for use in operations. An instantiated object of the portfolio **1002** represents a particular collection of web bookmarks.

FIG. 4 depicts an exemplary C++ class skeleton providing an object-oriented representation of a collection of web bookmarks. An instantiated object of the portfolio **1002** provides collections of objects for each of notices, topics, resources, and words. These collections are under the memory management of the portfolio **1002**. The set portfolio-notices **1020**

collects objects of the notice-class **1074**. The set portfolio-resources **1024** collects objects of the resource-class **1070**. The set portfolio-topics **1022** collects objects of the topic-class **1072**. A set portfolio-words **1110** collects objects of the word-class **1076**.

The portfolio **1002** provides a convenient site for classification services which are used in the computation of topics from notice descriptions. In an alternative embodiment, these computations could be provided as part of the classifier **1016** or in a distinct class or service. The portfolio **1002** computes a canonical word-type from supplied text. The portfolio **1002** computes a canonical topic from a supplied topic. The portfolio **1002** computes genera for a supplied topic.

The portfolio **1002** provides a computation canonical-word **1112** which computes a canonical object of the word-class **1076** from supplied text. In the computation, the supplied text is standardized; the standardization may include letter case, stemming, synonym preferences, etc. If no object of the word-class **1076** has previously been associated with the standardized text, a new object of the word-class **1076** is constructed and associated with the standardized text. The associations of standardized text with canonical objects of the word-class **1076** are maintained by a text-word-map **1114**. The associated object of the standardized text provides the computed canonical word.

The portfolio **1002** provides a computation canonical-topic **1116** which computes a canonical object of the topic-class **1072** from a supplied object of the topic-class **1072**. A standardized identifier for the canonical topic is computed from a concatenation of the text of the objects of the word-class **1076** associated with the supplied topic via the supplied topic's topic-words-sequence **1094**. If no topic has previously been associated with the standardized identifier, the supplied topic is associated with the standardized identifier. The associations of standardized identifiers with canonical objects of the topic-class **1072** are maintained by a text-topic-map **1118**. Genera are separately computed for the supplied topic, as described below. The supplied topic provides the computed canonical topic. Otherwise, where a topic has been previously associated with the standardized identifier, the supplied topic is deleted, and the previously associated topic provides the computed canonical topic.

The portfolio **1002** provides a computation topic-genera-computation **1120**, which computes genera for a supplied object of the topic-class **1072**. The supplied topic has an associated sequence of words, the topic-words-sequence **1094**. If the associated sequence of words has more than one word, a prefix genus topic is formed from the associated sequence of words with the last word omitted. A suffix genus topic is formed from the associated sequence of words with the first word omitted. The prefix and suffix genera are each standardized to a canonical topic, via the canonical-topic **1116**. The canonical prefix and suffix genera are associated with the supplied topic.

FIG. 5 depicts an exemplary computation of genera from a topic. An instance of the topic-category **1018** is depicted at the base of the figure, for which the topic-words-association **1060** includes instances of the word-category **1038** respectively corresponding to the texts "web", "based", "bookmark", and "manager". A prefix genus is computed, including instances of the word-category **1038** respectively corresponding to the texts "web", "based", and "bookmark". A suffix genus is computed, including instances of the word-category **1038** respectively corresponding to the texts "based", "bookmark", and "manager". Canonical topics are obtained for the prefix and suffix genera via the canonical-topic **1116**. The genus computation is invoked recursively in the canonical-

## 11

topic **1116** when a new canonical topic is determined. The remainder of the genera graph shown in the Figure is thus constructed if it does not already exist. An alternative embodiment treats a phrase as a set, not a sequence, and identifies genera with subsets, not subsequences.

The portfolio **1002** provides a computation topic-triviality **1122** which determines the triviality of an object of the topic-class **1072**. A topic is trivial if it has one or less associated resources, or if any of its species has as many associated resources as the topic.

## 7 Discourse

The bookmark manager **1000** includes a formal language **1124** which permits a textual representation of a collection of web bookmarks. The language **1124** consists of declarative discourse expressed in the antic meta language, which is described in U.S. patent application Ser. No. 11/023,205, "Method of Processing Databases", filed 2004Dec., 24, by the present inventor, incorporated herein by reference.

As an application of the antic meta language, the language **1124** consists of expressions which instantiate entities and interrelate entities in declarations. The entities of the discourse represent instances of the categories of the model **1036** as well as textual entities specifying the values of properties. An entity may optionally be associated with unique text; for entities representing instances, the unique text is an identifier for the instance. For entities representing property values, the text represents the value of the property.

A declaration includes a subject entity and a relation; an optional object entity may also be included. An entity may represent an instance or the value of a property. The relations of the discourse represent relationships specifying categories and features of the instances. The declarations of the discourse specify category membership of the instances, properties of the instances, and associations between instances. Expressions in the discourse permit more than one declaration to be economically expressed by combining multiple subjects, predicates, and objects.

FIG. 6 depicts relations that characterize an exemplary declarative language representing a bookmark collection. The language **1124** is characterized by the particular relations which indicate category membership, properties, and associations.

An is-word-characteristic **1126** indicates membership in the word-category **1038**. A word-has-text-relation **1128** specifies the word-text-property **1062** for an instance of the word-category **1038**. A word-has-topic-relation **1130** specifies the word-topics-association **1066** for an instance of the word-category **1038**.

An is-topic-characteristic **1132** indicates membership in the topic-category **1018**. A topic-has-text-relation **1134** specifies the topic-text-property **1050** for an instance of the topic-category **1018**. A topic-has-word-relation **1136** specifies the topic-words-association **1060** for an instance of the topic-category **1018**. A topic-has-genus-relation **1138** specifies the topic-genera-association **1056** for an instance of the topic-category **1018**. A topic-has-species-relation **1140** specifies the topic-species-association **1058** for an instance of the topic-category **1018**. A topic-has-resource-relation **1142** specifies the topic-resources-association **1054** for an instance of the topic-category **1018**.

An is-notice-characteristic **1144** indicates membership in the notice-category **1004**. A notice-has-date-relation **1146** specifies the notice-date-property **1040** for an instance of the notice-category **1004**. A notice-has-resource-relation **1148** specifies the notice-resource-association **1008** for an instance of the notice-category **1004**. A notice-has-description-relation

## 12

tion **1150** specifies the notice-description-property **1012** for an instance of the notice-category **1004**. A notice-has-topic-relation **1152** specifies the notice-topics-association **1042** for an instance of the notice-category **1004**.

An is-resource-characteristic **1154** indicates membership in the resource-category **1010**. A resource-has-notice-relation **1156** specifies the resource-notices-association **1046** for an instance of the resource-category **1010**. A resource-has-topic-relation **1158** specifies the resource-topics-association **1048** for an instance of the resource-category **1010**.

## 8 Archive

The archive **1026** represents a collection of bookmarks by describing an instantiation of the model **1036** for persistent storage in digital media, such as an operating system file. The archive **1026** uses the language **1124** to represent a bookmark collection.

FIG. 7 depicts an exemplary declarative discourse representing words. A words-discourse **1160** declares words and indicates the text for each word. The words-discourse **1160** includes expressions representative of instances of the word-category **1038**. Three such expressions are shown in the Figure. In the first expression, a subject entity identified by the text "Word-web" is predicated on the is-word-characteristic **1126**, thereby indicating membership in the word-category **1038**. After a semicolon, which indicates that another predicate is supplied for the same subject entity, the word-has-text-relation **1128** expresses the property word-text-property **1062**; in this expression, the property value is specified as the text "web". The expression is terminated with a period. The other expressions are similar in structure, with distinct identifiers for the entity representing the word-category **1038**, and distinct values for the word-text-property **1062**.

FIG. 8 depicts an exemplary declarative discourse representing topics. A topics-discourse **1162** declares topics, indicates the text for each topic, the words associated with the topic, and a prefix genus and a suffix genus, if any. The topics-discourse **1162** includes expressions representative of instances of the topic-category **1018**. Two such expressions are shown in the Figure. In the first expression, a subject entity identified by the text "Topic-web-based-manager" is predicated on the is-topic-characteristic **1132**, thereby indicating membership in the category topic-category **1018**. After the semicolon, the topic-has-text-relation **1134** expresses the topic-text-property **1050**. This expression specifies the value of the property as the text "web based manager".

Another semicolon delimits a distinct predicate, in which the topic-has-word-relation **1136** expresses the topic-words-association **1060**. In this predicate, three objects are indicated, separated by commas. Each object implies a distinct declaration, with common subject and relation. The objects predicated on the topic-words-association **1060** are instances of the word-category **1038**. In this predicate, the particular instances of the word-category **1038** are identified by "Word-web", "Word-based", and "Word-manager", respectively.

Another semicolon delimits a distinct predicate, in which the topic-has-genus-relation **1138** expresses the topic-genera-association **1056**. In this predicate, two objects are indicated. The objects predicated are instances of the topic-category **1018**, identified by "Topic-web-based" and "Topic-based-manager". These topics are the prefix and suffix genera determined by the topic-genera-computation **1120**.

FIG. 9 depicts an exemplary declarative discourse representing resources. A resources-discourse **1164** declares resources and indicates the notices associated with each resource. The date, description, and associated topics for each notice are declared in the resources discourse. The resources-



## 13

discourse **1164** includes expressions representative of instances of the resource-category **1010**. One such expression is shown in the Figure. In the expression, a subject entity identified by the text “http://www.n-gon.com . . .” is predicated on the resource-has-notice-relation **1156**, which expresses the resource-notices-association **1046**. Two objects are indicated in this predicate, representing instances of the notice-category **1004**. The notice objects are anonymously expressed using curly brackets, which indicate an entity lacking optional text. There is no particular need to name instances of the notice-category **1004**.

The instances of the notice-category **1004** which are represented by the objects are characterized by provision of date, description, and associated topics. In the first object, the anonymous entity representing an instance of the notice-category **1004** is predicated on the notice-has-date-relation **1146**, which expresses the notice-date-property **1040**. The property value is indicated at “2001-10-22”. The anonymous entity is predicated on the notice-has-description-relation **1150**, which expresses the notice-description-property **1012**. The property value is indicated as “Web-based manager . . .”. The anonymous entity is predicated on the notice-has-topic-relation **1152**, which expresses the notice-topics-association **1042**. The objects of the notice-has-topic-relation **1152** are representative of instances of the topic-category **1018**. In this predicate, four objects are indicated, of the which the first two are identified as “Topic-b” and “Topic-web-based-manager”.

FIG. **10** depicts an exemplary declarative discourse representing notices. Additional notices intended for incorporation to a bookmark collection are provided in a notices-discourse **1006**. The notices-discourse **1006** includes a sequence of expressions, each of which describes a notice with a date, resource, and description. Two such expressions are shown in the Figure. The first expression describes an anonymous entity, representing an instance of the notice-category **1004**. The entity is predicated on the notice-has-date-relation **1146**, which expresses the notice-date-property **1040**. The property value is indicated at “2001-10-22”. The entity is also predicated on the notice-has-resource-relation **1148**, which expresses the notice-resource-association **1008**. The object indicates the associated instance of the resource-category **1010** identified by the text “http://www.n-gon.com . . .”. The entity is also predicated on the notice-has-description-relation **1150**, which expresses the notice-description-property **1012**. The property value is indicated as “Web-based manager . . .”. The notices described in this discourse have not yet been analyzed to determine associated topics.

## 9 Writer

FIG. **11** depicts the context for an exemplary writer which views a portfolio and writes an archive. An exemplary embodiment of the bookmark manager **1000** includes a writer **1028** which writes an archive representative of a bookmark collection. The writer **1028** operates on a portfolio **1002**, computing an archive **1026**. The portfolio **1002** is unaffected by the operation.

FIG. **12** depicts an exemplary writer which views an object-oriented representation of a collection of web bookmarks and writes an archive. The writer **1028** writes the words-discourse **1160**. For each instance of the word-class **1076** in the portfolio-words **1110** of the supplied portfolio **1002**, the word-id-text **1106** and the word-text-text **1104** are written, suitably related via the is-word-characteristic **1126** and the word-has-text-relation **1128**, respectively.

The writer **1028** writes the topics-discourse **1162**. For each instance of the topic-class **1072** in the portfolio-topics **1022** of the supplied portfolio **1002**, the topic-id-text **1086** and the

## 14

topic-text-text **1084** are written, suitably related via the is-topic-characteristic **1132** and the topic-has-text-relation **1134**, respectively. If the topic-words-sequence **1094** is non-empty, a predicate topic-has-word-relation **1136** is written, and, for each associated object of the word-class **1076**, the word-id-text **1106** is written. If the topic-genera-set **1090** is non-empty, a predicate topic-has-genus-relation **1138** is written, and, for each associated object of the topic-class **1072**, the topic-id-text **1086** is written.

The writer **1028** writes the resources-discourse **1164**. For each object of the resource-class **1070** in the portfolio-resources **1024** of the supplied portfolio **1002**, the resource-URI-text **1078** is written, serving as a unique identifier for the resource instance. If the resource-notices-set **1080** is non-empty, a predicate resource-has-notice-relation **1156** is written, and, for each associated object of the notice-class **1074**, the notice-date-text **1096** is written, predicated on the notice-has-date-relation **1146**. The notice-description-text **1098** is also written, predicated on the notice-has-description-relation **1150**. If the notice-topics-set **1102** is non-empty, a predicate notice-has-topic-relation **1152** is written, and, for each associated object of the topic-class **1072**, the topic-id-text **1086** is written.

## 10 Reader

An exemplary embodiment of the bookmark manager **1000** includes a reader **1030**, which mediates the construction of the interlinked object-oriented data structures of the portfolio **1002** from an archive **1026** in the language **1124**.

FIG. **13** depicts an exemplary reader which constructs an object-oriented representation of a collection of web bookmarks from a declarative discourse. A reader **1030** operates on an archive **1026**, editing a portfolio **1002**. The archive **1026** is unaffected by the operation.

The reader **1030** uses a dispatcher **1166** which contains a collection instantiators **1168**, a collection receivers **1170**, a collection assignors **1172**, and a collection associators **1174**. The elements of these collections are responsive to declarations in the archive **1026** discourse. The instantiators, assignors, and associators mediate the population of the portfolio **1002**. The dispatcher **1166** is further augmented with declarations establishing useful meta relations.

The dispatcher **1166** contains the collection instantiators **1168**. Each instantiator is responsible for instantiation of an instance of a particular category in response to dispatch of a declaration in which a subject entity is combined with a particular characteristic relation. Each instantiator additionally provides a resolution service in which an associated instance, if any, is provided for a supplied entity.

FIG. **14** depicts exemplary instantiators, the characteristic relations to which they are responsive, and the categories for which they provide instances. A word-instantiator **1176** provides instantiation for the word-category **1038**, responsive to the is-word-characteristic **1126**. A topic-instantiator **1178** provides instantiation for the topic-category **1018**, responsive to the is-topic-characteristic **1132**. A resource-instantiator **1180** provides instantiation for the resource-category **1010**, responsive to the is-resource-characteristic **1154**. A notice-instantiator **1182** provides instantiation for the notice-category **1004**, responsive to the is-notice-characteristic **1144**.

The dispatcher **1166** contains the collection receivers **1170**. Each receiver is responsible for assigning the text which uniquely identifies a particular entity to a text member in an object which represents an instance of a category in an object-oriented data structure. Receivers are responsive to dispatch of characteristic relations.

## 15

FIG. 15 depicts exemplary text receivers, the characteristic relations to which they are responsive, and the properties for which they receive entity text. A word-id-receiver 1184, responsive to the is-word-characteristic 1126, receives entity text for the word-id-property 1064. A topic-id-receiver 1186, responsive to the is-topic-characteristic 1132, receives text for the topic-id-property 1052. A resource-url-receiver 1188, responsive to the is-resource-characteristic 1154, receives text for the resource-URI-property 1044.

The dispatcher 1166 contains the collection assignors 1172. Each assignor is responsible for assignment of properties in instantiated instances of a particular category in response to dispatch of a declaration in which a subject entity is coupled to a textual object via a particular relation.

FIG. 16 depicts exemplary assignors, the relations to which they are responsive, and the properties for which they provide assignments. A word-text-assignor 1190, responsive to the word-has-text-relation 1128, implements the word-text-property 1062. A topic-text-assignor 1192, responsive to the topic-has-text-relation 1134, implements the topic-text-property 1050. A notice-date-assignor 1194, responsive to the notice-has-date-relation 1146, implements the notice-date-property 1040. A notice-description-assignor 1196, responsive to the notice-has-description-relation 1150, implements the notice-description-property 1012.

The dispatcher 1166 contains the collection associators 1174. Each associator is responsible for association of instances of particular subject and object categories in response to dispatch of a declaration in which a subject entity is coupled to an object entity via a particular relation.

FIG. 17 depicts exemplary associators, the relations to which they are responsive, and the associations which they implement. A word-topic-associator 1198, responsive to the word-has-topic-relation 1130, implements the word-topics-association 1066. A topic-genus-associator 1200, responsive to the topic-has-genus-relation 1138, implements the topic-genera-association 1056. A topic-species-associator 1202, responsive to the topic-has-species-relation 1140, implements the topic-species-association 1058. A topic-resource-associator 1204, responsive to the topic-has-resource-relation 1142, implements the topic-resources-association 1054. A topic-word-associator 1206, responsive to the topic-has-word-relation 1136, implements the topic-words-association 1060. A notice-resource-associator 1208, responsive to the notice-has-resource-relation 1148, implements the notice-resource-association 1008. A notice-topic-associator 1210, responsive to the notice-has-topic-relation 1152, implements the notice-topics-association 1042. A resource-notice-associator 1212, responsive to the resource-has-notice-relation 1156, implements the resource-notices-association 1046. A resource-topic-associator 1214, responsive to the resource-has-topic-relation 1158, implements the resource-topics-association 1048.

FIG. 18 depicts exemplary declarations establishing meta relations in the dispatcher. A declaration establishes the complementarity of the topic-species-association 1058 and topic-genera-association 1056. A declaration establishes the complementarity of the topic-resources-association 1054 and resource-topics-association 1048. A declaration establishes the complementarity of the topic-words-association 1060 and word-topics-association 1066. A declaration establishes the complementarity of the resource-notices-association 1046 and notice-resource-association 1008.

## 11 Update

FIG. 19 depicts an exemplary updater in which a notices discourse is read and a portfolio is edited to incorporate the

## 16

notices. The bookmark manager 1000 includes a updater 1014, which reads the notices-discourse 1006, editing a portfolio 1002. The updater 1014 makes use of a notice-accumulator 1216. The notice-accumulator 1216 is a custom responder which is engaged while processing the notices-discourse 1006. The notice accumulator is dispatched on the is-notice-characteristic 1144. The notice accumulator collects objects of the notice-class 1074 as they are instantiated during the processing of the discourse. When the discourse processing is complete, the notice-description-text 1098 of each accumulated notice is processed by the classifier 1016 to determine topics to be associated with each accumulated notice.

## 12 Classifier

An exemplary embodiment of the bookmark manager 1000 includes the classifier 1016, which provides an automatic determination of topics for classification of web resources from natural language descriptions. The classifier 1016 is used in the updater 1014 which incorporates new notices into an existing portfolio 1002.

FIG. 20 depicts an exemplary grammar for an exemplary classifier which computes topics from notice descriptions. The classifier 1016 processes a textual description in the context of a particular portfolio 1002 and a particular object of the notice-class 1074. The classifier may determine one or more objects of the topic-class 1072 for the notice-topics-set 1102. The classifier uses a formal grammar 1218 to process natural language textual descriptions.

A description is parsed into lexical tokens (terminals) in accordance with the grammar 1218. A terminal white-space 1220 represents white space. A terminal punctuation 1222 represents ordinary punctuation. A terminal dash 1224 represents a special case of punctuation, recognizing the phrase-like characteristic of dash-connected word pairs. An alternative embodiment might similarly provide for phrase-like characteristics of other embedded punctuation, including, e.g. slash.

A terminal function-word 1226 represents function words, which are relatively free of content, e.g. "the", "a", "of", etc.

A terminal content-word 1228 represents content words which are indicative of content. Content words include any words which are not recognized as function words.

A complete description is represented by a nonterminal start 1230. A sequence of content words, corresponding to a phrase in natural language, is represented by a nonterminal topic 1232. A delimiter of a sequence of content words is represented by a nonterminal stop 1234.

The nonterminal start 1230 represents a complete description. In a first start rule, an empty description is accepted; no action is required. In a second start rule, a description followed by a topic 1232 is accepted; the accepted topic 1232 is separately processed as described below. In a third start rule, a description followed by a topic 1232 followed by a stop 1234 is accepted; the accepted topic 1232 is separately processed as described below. In a fourth start rule, a description followed by a topic 1232 followed by a white-space 1220 is accepted; the accepted topic 1232 is separately processed as described below. In a fifth start rule, a description followed by a stop 1234 is accepted; no action is required. In a sixth start rule, a description followed by a white-space 1220 is accepted; no action is required.

The nonterminal topic 1232 represents a sequence of content words, corresponding to a phrase in natural language. In a first topic rule, a topic is initialized by a single terminal content-word 1228. In a second topic rule, content is appended to a topic, where a nonterminal topic is followed by

17

a terminal white-space **1220** and a terminal content-word **1228**. In a third topic rule, content is appended to a topic, where a nonterminal topic is followed by a terminal dash **1224** and a terminal content-word **1228**. In other embodiments, other embedded punctuation characters, such as slash, are also accepted for continuation of derivations of the topic **1232**.

The nonterminal stop **1234** represents a delimiter for a sequence of content words representing a topic. In a first stop rule, a terminal punctuation **1222** provides a delimiter. In a second stop rule, a terminal dash **1224** provides a delimiter. In a third stop rule, a terminal function-word **1226** provides a delimiter. In other embodiments, other special-case punctuation would similarly derive stop nonterminals outside of phrase-like context.

The nonterminal topic **1232** is associated with a sequence of terminal content-word **1228**. When a topic is accepted, each associated terminal content-word **1228** is processed to determine a canonical instance of the word-class **1076**; the processing is provided by the canonical-word **1112**. The sequence of word instances may then be used to instantiate an instance of the topic-class **1072**. The topic instance is resolved to a canonical instance of the topic-class **1072**; the processing is provided by the canonical-topic **1116**.

FIG. **21** depicts an example of the exemplary classifier processing a description in natural language to several topics. The notice-description-property **1012** has a value "b.—Web-based manager for bookmarks using XML, Perl". In the lexical analysis stage, the text value is processed to a sequence of terminal tokens, included the content-word **1228** corresponding to the text "b", the punctuation **1222** corresponding to the text ".", the white-space **1220** corresponding to the text " ", etc. In the parse stage, terminals are accumulated to form the topic-category **1018** corresponding to the text "b", including the instance of the word-category **1038** corresponding to the text "b". Terminals are accumulated to form the instance of the topic-category **1018** corresponding to the text "web based manager", including the sequence of instances of the word-category **1038** corresponding to the respective texts "web", "based", and "manager".

### 13 Presentation

The bookmark manager **1000** includes a presenter **1032**, which provides an exemplary presentation of the collection of web bookmarks as a collection of interlinked HTML resources.

FIG. **22** depicts an exemplary presenter, which reads an archive, edits a portfolio, and writes a presentation. The presenter **1032** reads an archive **1026**, editing a portfolio **1002**, then processes the portfolio **1002** to write a presentation **1034** of the portfolio **1002** contents. The display computation uses a closure-dispatcher **1236**, a specialization of the dispatcher **1166**. The presentation includes a chronology-presentation **1238** of notices, a resource-presentation **1240** for each individual resource, a topic-presentation **1242** for each individual topic, a ranking-presentation **1244** of topics, a thesaurus-presentation **1246** of topics, and an index-presentation **1248** of topics.

The closure-dispatcher **1236** specializes the dispatcher **1166**. The specialized dispatcher includes a notice-resource-topic-associator **1250** to associate an instance of the resource-category **1010** with one or more instances of the topic-category **1018** via an instance of the notice-category **1004**. On dispatch of the association of a notice with a resource, via the resource-has-notice-relation **1156**, the custom responder **1158** instantiates the implied associations between the resource and the topics associated with the notice.

18

FIG. **23** depicts exemplary declarations establishing meta relations in the closure dispatcher. The specialized dispatcher is also augmented with meta quality declarations which qualify the topic-genera-association **1056** and the topic-species-association **1058** as transitive associations. The transitivity meta property results in the closure of genera and species topic associations for use in display, although only suffix and prefix genus associations are recorded in the archive **1026**.

FIG. **24** depicts an exemplary presentation of a chronology of notices from a bookmark collection. The chronology-presentation **1238** presents the instances of the notice-category **1004** in the portfolio **1002**. The notices are aggregated by the notice-date-property **1040**. The aggregates are presented in reverse chronological order (newest first). For each aggregate of notices on a particular date, a chronology-date-division **1252** is generated, titled by the date. The individual notices in the aggregate are presented in a list, one element per notice, with a chronology-resource-link **1254** to the resource-presentation **1240** corresponding to the notice's resource. The link text is supplied by the notice-description-property **1012**.

FIG. **25** depicts an exemplary presentation of a resource from a bookmark collection. The resource-presentation **1240** presents an instance of the resource-category **1010** in the portfolio **1002**. Each resource in the portfolio **1002** is presented individually. The resource presentation includes a display-resource-link **1256** to the referenced resource, as specified by the value of the resource-URI-property **1044**. The resource presentation further includes a display-resource-notices-list **1258**, indicating the associated instances of the notice-category **1004**, with links back to the appropriate chronology-date-division **1252**. Also included in the resource presentation is a display-resource-topics-list **1260**, indicating the non-trivial topics associated with the resource. Topic triviality is determined by the topic-triviality **1122**. For each non-trivial associated topic, a link is provided to the topic's topic-presentation **1242**.

FIG. **26** depicts an exemplary presentation of a topic from a bookmark collection. The topic-presentation **1242** presents a non-trivial instance of the topic-category **1018** in the portfolio **1002**. Each non-trivial topic in the portfolio **1002** is presented individually. The topic presentation includes a title, incorporating the topic text, a display-topic-search **1262** to a web search for the topic text, and display-topic-index-links **1264** to the division in the index-presentation **1248** for each word associated with the topic. The topic presentation further includes a display-topic-thesaurus-link **1266** to the division for the topic in the thesaurus-presentation **1246**, a display-topic-genera-list **1268**, containing links to the topic-presentation **1242** for each genus of the topic, if any, as indicated by the topic-genera-association **1056**. The topic presentation also includes a display-topic-species-list **1270**, containing links to the topic-presentation **1242** for each species for the topic, if any, as indicated by the topic-species-association **1058**. The topic presentation also includes a display-topic-resources-list **1272**, containing links to the resource-presentation **1240** for each resource associated with the topic. In an alternative embodiment, links are provided into the chronology-presentation **1238** for each instance of the notice-category **1004** from the description of which the topic was obtained.

FIG. **27** depicts an exemplary presentation of a ranking of topics for a bookmark collection. The ranking-presentation **1244** presents the non-trivial instances of the topic-category **1018** in the portfolio **1002**. A ranking of non-trivial topics is presented. Topics are ranked according to declining count of associated resources (alternatively, associated notices). Each

19

topic in the ranking is presented as a ranking-topic-link **1274** to the particular topic-presentation **1242** for the topic. The count of associated resources (alternatively, associated notices) is also presented.

FIG. **28** depicts an exemplary presentation of a taxonomy of topics for a bookmark collection. The thesaurus-presentation **1246** presents the non-trivial instances of the topic-category **1018** in the portfolio **1002**. Topics in the taxonomy are ordered alphabetically by topic text. For each non-trivial topic in the portfolio **1002**, the topic text and count of associated resources is presented in a thesaurus-topic-link **1276** to the particular topic-presentation **1242** for the topic. Non-trivial genera are presented in a thesaurus-genera-list **1278**, containing links within the taxonomy presentation. Non-trivial species are presented in a thesaurus-species-list **1280**, containing links within the taxonomy presentation.

FIG. **29** depicts an exemplary presentation of an index of topics for a bookmark collection. The index-presentation **1248** presents the non-trivial instances of the topic-category **1018** in the portfolio **1002**. For each non-trivial topic, one or more index entries are provided. An index-word-entry **1282** is determined by cyclic permutation of the sequence of words associated with the topic. Each entry links to the particular topic-presentation **1242** for the topic. A index-word-division **1284** is an aggregate of entries sharing a leading word. The index presents the entries in alphabetic order.

I claim:

1. An apparatus for managing a collection of web bookmarks, comprising:

a computing device configured to execute software comprising:

a reader, configured to process a computer-readable archive representing a collection of web bookmarks to produce an object-oriented data structure representing said collection of web bookmarks, said data structure comprising an object-oriented representations of notice events, each notice event comprising

a reference to a web resource, and  
a natural language description of said web resource;

a classifier, configured to process notice event, comprising

means for parsing said natural language description to obtain at least one sequence of at least one content word;

means for associating a topic category with said sequence;

means for recursively computing generic topics using non-empty subsequences of content words from the sequence associated with the topic category, wherein the generic topics are used to automatically construct a taxonomy of topics for classifying web resources;

means for associating said reference to a web resource with said topic category; and

a presenter, configured to process said object-oriented data structure to produce a presentation representing said collection of web bookmarks.

2. The apparatus of claim 1, wherein:

said notice event further comprises a date; and

said presenter further comprises means for presenting a plurality of said notice representation in any of forward and reverse chronological order, according to said associated date.

3. The apparatus of claim 1, wherein:

said presentation comprises any of

20

a presentation of said web resource, including presentation of said topic category associated with said web resource; and

a presentation of said topic category, including presentation of said web resource associated with said topic category, and further including a presentation of said taxonomy of topics.

4. The apparatus of claim 1, further comprising:

means for standardizing the form of a word from said sequence of at least one content word, including any of means for normalizing case, means for stemming, and means for substitution of synonyms.

5. The apparatus of claim 1, said parsing means further comprising:

means for performing lexical analysis to decompose said natural language description to a token sequence of one or more instances of terminal tokens, said instances of terminal tokens comprising  
instances of a space token,  
instances of a punctuation token,  
instances of a function word token,  
and instances of a content word token; and

means for performing syntactic analysis on said token sequence to obtain said at least one sequence of at least one content word, said sequence obtained by accumulation of a maximal subsequence of instances of the content word token, interspersed with instances of the space token.

6. The apparatus of claim 5, wherein:

said instances of terminal tokens further comprise instances of a dash token, and

said means for syntactic analysis further comprises means for accumulating maximal subsequences of instances of the content word token interspersed with instances of any of the space token and the dash token.

7. The apparatus of claim 1, wherein:

said computer-readable archive is a declarative discourse, and

said reader further comprises means for responding to declarations of said declarative discourse.

8. The apparatus of claim 7, said means for responding to declarations further comprising:

at least one instantiator responsive to declarations including a characteristic relation, said instantiator configured to instantiate an instance of an object-oriented class;

at least one receiver responsive to declarations including a characteristic relation, said receiver configured to associate text identifying a subject entity with a member of an instance of an object-oriented class;

at least one associator responsive to declarations including an association relation; said associator configured to associate a first instance of an object-oriented class with a member of an instance of a second object-oriented class; and

at least one assignor responsive to declarations including a property relation, said assignor configured to associate a scalar value with a member of an instance of an object-oriented class.

9. The apparatus of claim 1, further comprising:

a writer configured to process said object-oriented data structure to produce said computer-readable archive representing said collection of web bookmarks.

10. The apparatus of claim 9, wherein:

said computer-readable archive is a declarative discourse.

11. A method for processing a collection of web bookmarks, comprising the steps of:

21

receiving at least one bookmark notice, said notice comprising  
 a reference to a web resource, and  
 a natural language description of said web resource;  
 parsing said natural language description to obtain at least  
 one sequence of at least one content word;  
 associating a topic category with said sequence;  
 recursively computing generic topics using non-empty  
 subsequences of content words from the sequence asso-  
 ciated with the topic category, wherein the generic topics  
 are used to automatically construct a taxonomy of topics  
 for classifying web resources;  
 associating said web resource with said topic category;  
 presenting the association of said web resource with said  
 topic category; and  
 presenting the association of said topic category with said  
 taxonomy of topics.  
**12.** The method of claim **11**, further comprising the step of:  
 standardizing the form of a word from said sequence of at  
 least one content word, including any of normalizing  
 case, stemming, and substitution of synonyms.  
**13.** The method of claim **11**, further comprising the steps  
 of:  
 associating a date with each of said at least one bookmark  
 notice; and  
 presenting a plurality of said at least one bookmark notice  
 in any of forward and reverse chronological order,  
 according to said associated date.  
**14.** The method of claim **11**, wherein said parsing step  
 further comprising the steps of:  
 performing lexical analysis to decompose said natural lan-  
 guage description to a token sequence of one or more  
 instances of terminal tokens, said instances of terminal  
 tokens comprising  
 instances of a space token,  
 instances of a punctuation token,  
 instances of a function word token, and  
 instances of a content word token; and  
 performing syntactic analysis on said token sequence to  
 obtain said at least one sequence of at least one content  
 word, said sequence obtained by accumulation of a  
 maximal subsequence of instances of the content word  
 token, interspersed with instances of the space token.  
**15.** The method of claim **14**, wherein said instances of  
 terminal tokens further comprising  
 instances of a dash token,

22

and said syntactic analysis step further accumulating maxi-  
 mal subsequences of instances of the content word  
 token, interspersed with instances of any of the space  
 token and the dash token.  
**16.** A method for processing a collection of resource  
 notices to construct a topic taxonomy and classify resources  
 to topics, comprising the steps of:  
 receiving at least one notice, said notice comprising:  
 a reference to a resource, and  
 a natural language description of said resource;  
 parsing said natural language description to obtain at least  
 one sequence of at least one content word;  
 associating a topic category with said sequence;  
 recursively computing generic topics using non-empty  
 subsequences of content words from the sequence asso-  
 ciated with the topic category, wherein the generic topics  
 are used to automatically construct a taxonomy of topics  
 for classifying resources to topics; and  
 associating said resource with said topic category.  
**17.** The method of claim **16**, further comprising the step of:  
 standardizing the form of a word from said sequence of at  
 least one content word, including any means of normal-  
 izing case, stemming, and substitution of synonyms.  
**18.** The method of claim **16**, wherein said parsing step  
 further comprising the steps of:  
 performing lexical analysis to decompose said natural lan-  
 guage description to a token sequence of one or more  
 instances of terminal tokens, said instances of terminal  
 tokens comprising  
 instances of a space token,  
 instances of a punctuation token,  
 instances of a function word token, and  
 instances of a content word token; and  
 performing syntactic analysis on said token sequence to  
 obtain said at least one sequence of at least one content  
 word, said sequence obtained by accumulation of a  
 maximal subsequence of instances of the content word  
 token, interspersed with instances of the space token.  
**19.** The method of claim **18**, wherein said instances of  
 terminal tokens further comprising  
 instances of a dash token,  
 and said syntactic analysis step further accumulating maxi-  
 mal subsequences of instances of the content word  
 token, interspersed with instances of any of the space  
 token and the dash token.

\* \* \* \* \*